

LOBADUR



Lobadur® Lacquers

Getting the best result
WITHOUT roller marks!

LOBA
WS Lacquers
100%
Free of
roller marks



®

Lobadur® Lacquers

Getting the best results



INTRODUCTION

The LOBA® finishing system consists of 3 products for all wooden floors. The primer is universally applicable and has similar properties to a lacquer. The lacquers have an extremely good flowing quality and durability when compared with our competitors. Two finish effects will be available: matt and satin. And last but not least, the end result should be

100% free of roller marks!

LOBA® SYSTEM

THE MOST IMPORTANT PRODUCT FEATURES ARE:

- **Excellent flow properties / 100% free of roller marks**
The visibility of roller marks is reduced due to high flow properties and the long open time of all LOBADUR® products.
- **Primer with a film coating**
It is a good filling primer that forms a film coat. It also provides excellent results on absorbent wooden floors.
- **Beautiful deep natural colour**
Certainly no pale effect
- **Low solvent and free of NMP**
The LOBADUR® system conforms to the OPS-legislation and therefore contains less than 10% solvent. Additionally, all products are free of NMP.
- **Reduces the working of edge binding**
Extremely important in the case of floating floors
- **High durability**
High viscosity filling primer and lacquers result in a substantial finish that has sufficient body. The lacquers are based on high-grade polyurethane binding materials and so an unequalled durability is guaranteed.

WITHOUT roller marks!

ASSORTMENT

LOBADUR® WS EasyPRIME

The LOBADUR® WS EasyPrime really has unique flow properties. Because of this, it can be applied like a lacquer. The primer flows like water, and can be applied in a very fine consistency. The appearance of roller marks is significantly reduced. The product is also suitable for irregular absorbing wooden floors like beech and maple. The end result looks first-class! Indeed, the primer can be applied quickly and easily to most wooden floors without leaving visible roller marks and a perfect result is guaranteed. The main reason for this is that this product produces a film coat and isolates the working surface, producing a deep natural colour. The LOBADUR® WS EasyPrime is optimally applicable on all regular sorts of wood, Iroko/Kambala excluded.

LOBADUR® Viva & LOBADUR® Fusion 2K

It's a simplified choice of two lacquers in this new range: LOBADUR® Viva and LOBADUR® Fusion 2K. Both lacquers can be used on the vast majority of known wood species (just like the LOBADUR® WS EasyPrime) and make the choice simple. The main difference between this lacquer range and the competition is the durability. LOBADUR® Viva is suitable for all standard applications; LOBADUR® Fusion 2K is especially designed for floors with a very high load usage as it has an extremely high resistant final finish. Both LOBADUR® Viva and LOBADUR® Fusion 2K are available in matt and satin.

ACCESSORIES

- **SPATULA**
For applying the LOBADUR® Viva and LOBADUR® Fusion 2K with a spatula
- **ROLLER**
For applying the LOBADUR® WS EasyPrime, LOBADUR® Viva and LOBADUR® Fusion 2K with a roller.

LOBA AND LECOL: TOGETHER WE ARE SIMPLY THE BEST



There has been a relationship between Lecol and LOBA for 25 years. This relationship stands for the best quality for all wooden floors in the Netherlands, Belgium and the UK. The new LOBA® finishing system is a result of the long lasting relationship between LOBA and Lecol; both companies are continually searching for innovation and this system is the latest product of the partnership.

ADVICE AND INFORMATION

For more information about the LOBA® finishing system or if you are interested in a demonstration, please contact our Sales Department by calling on 0870 922 2837. Alternatively you can send an email to sales@lecoluk.com or visit our website www.lecoluk.com for the technical and safety sheets. With the latest products from Lecol, you can be absolutely sure that the parquet and wooden floors you deliver to your customer have been installed with New Generation products.



Lobadur® WS EasyPrime available in 5 lt.



Lobadur® Viva available in 5 lt.



Lobadur® Fusion 2K available in 5 kg.



Spatula



Roller

APPLICATION TABLE

PRODUCT
SIZE
PRODUCT TYPE
AVAILABLE IN
SUITABLE FOR EUROPEAN WOOD TYPES
SUITABLE FOR EXOTIC WOOD TYPES
SUITABLE FOR EXOTIC FSC WOOD TYPES
SUITABLE IN COMBINATION WITH LOBADUR® EasyPrime
ISOLATING SURFACE
COLOURING EFFECT
SUITABLE FOR DOMESTIC AREAS
SUITABLE FOR OFFICE AND COMMERCIAL AREAS
DRYING TIME AT 20°, 65% R.H. WITH GOOD VENTILATION

Lecol Lacquer System			
			
	LOBADUR® <i>EasyPrime</i>	LOBADUR® <i>Viva</i>	LOBADUR® <i>Fusion 2K</i>
	5 ltr	5 ltr	5 kg
	1 Component Primer	1 Component Lacquer	2 Component Lacquer
	NA	Matt / Satin	Matt / Satin
	++	++	++
	++	++	++
	++	++	++
	NA	++	++
	++	-	-
	-	-	-
	++	++	++
	++	-	++
	1-2 hours	3-4 hours	3-4 hours

- ++ Very Suitable
 + Suitable
 +/- Limited Suitable
 - Not Suitable
 . Not suitable for Inko Kambola

USAGE TABLE

	Mattgrade	Packaging/ usage per layer	Processing	Drying time per layer 20°C / 65% RH
LOBADUR® <i>EasyPrime</i>	NA	5 ltr = 40-50 m ² per layer	Roller, 1 layer	1 - 2 hours
LOBADUR® <i>Viva</i>	Satin Semi Gloss	5 ltr = 40-50 m ² per layer	Roller, 2 layers or: Spatula, 2 layers crossed wet in wet, thereafter rolling 1 layer	Approx 3 - 4 hours Approx 30 - 60 min. Approx 3 - 4 hours
LOBADUR® <i>Fusion 2K</i>	Satin Semi Gloss	1 kg = 8-10 m ² per layer 5 kg = 40-50 m ² per layer	Roller, 2 layers or: Spatula, 2 layers crossed wet in wet, thereafter rolling 1 layer	Approx 3 - 4 hours Approx 30 - 60 min. Approx 4 - 6 hours

EXPLANATION USAGE TABLE: THE LOBA® FINISHING SYSTEM SHOULD ALWAYS CONSIST OF A MINIMUM OF THREE LAYERS. ALWAYS APPLY ONE PRIMER LAYER WITH A ROLLER, THEREAFTER TWO COATS OF LOBADUR® VIVA OR LOBADUR® FUSION 2K (ROLLER).

Lecol
 Postbox 51 NL-5140 AB
 Waalwijk, The Netherlands
 Tel: 0070 922 2837
 Fax: +31 416 566 531
 sales@lecoluk.com
 www.lecoluk.com

